

ACRYLSEAL

A liquid-applied waterproofing acrylic, reinforced with acryl membrane to provide a seamless waterproofing system.

1. USES

- All types of Flashings.
- Parapet Walls.
- Flat roofs smaller than 500m².
- Re-waterproofing over existing waterproofing systems.
- Sealing joints, laps and roofing screws on corrugated roofs.

2. ADVANTAGES

- Excellent weathering properties.
- Tough and flexible.
- Excellent adhesion.

3. LIMITATIONS

Do not apply **Acrylseal** if rain is imminent.

4. COVERAGE

2.5 square metres per litre with membrane.

5. SURFACE PREPERATION

All surfaces should be sound, clean and free from any contaminants including rust.

6. APPLICATION

Priming

All surfaces except iron and steel, should be primed using **Acryl Prime**.
Iron and steel should be primed using a suitable corrosion resistant etch primer.

First Coat

Apply a generous coat of **Acrylseal** by brush or roller (1 litre/m²)
Bed the membrane into the wet coat, taking care to remove all air pockets and crease marks.
Overlaps must be a minimum of 50mm.

Second Coat

Immediately apply a second coat to fully saturate the membrane from top and bottom.

Final Coat

Once the second coat is touch dry apply final topcoat.

7. CLEANING

Uncured **Acrylseal** can be removed with water
Cured material can only be removed mechanically.

8. DISPOSAL

Dispose in accordance with local regulations.

9. HEALTH AND SAFETY

Safety data sheets –available on request

Shelf life	12 Month in unopened container.
Storage	Store under cover, and protect from frost.
Colour	Different colours are available.
Drying time	2-3 hours depending on conditions.
Cleaning	Uncured- water. Cured-Mechanical.
Coverage	2.5litre per square metres for full system.
Packaging	20litre, 5litre